

PTS-SAASM

Network Ready Precision Time System

GPS Disciplined Atomic Clock

- Network Time Server
- Dual Redundant Version Available
- Complete Remote Network Control using Standard Web Browser
- SA-ASM GPS Receiver
- 10MHz, 1PPS IRIG B, Serial and Time Codes
- Timing Accuracy < 40ns_{rms} to UTC
- 1PPS, Have Quick Inputs



The PTS-SAASM is a state of the art frequency instrument offering a wide range of features and time and frequency outputs accurate to < 40ns_{rms} to UTC (USNO) and 1x10⁻¹² respectively.

This new generation of network appliance is economical and reliable and offers complete remote control and monitoring via a web-browser based interface.

The PTS-SAASM can be used in either a single or dual redundant configuration and in conjunction with one of Brandywine Communications range of Distribution Amplifiers, such as the FTSU-100.

Applications for the popular PTS-SAASM include central time and frequency systems, satellite earth stations, military communication systems, and high availability network time servers.

An extremely accurate internal rubidium oscillator is used as the internal time base that drives all the time and frequency outputs. This rubidium oscillator is disciplined using an advanced control algorithm, ensuring superior holdover performance. The time constants of this algorithm are user-adjustable to suit specific applications.

A low cost rack adapter is available (not shown).

The PTS-SAASM utilizes a 12 channel P(Y) code SAASM GPS receiver. It may also be disciplined to an external 1PPS/HaveQuick time code source.

A 100baseT Ethernet port is provided which is used both for monitoring and control of the instrument and for Network Time Protocol. This interface supports both fixed and dynamic IP address assignment via DHCP.

In addition to configuring the PTS-SAASM, the built-in web browser provides information on GPS, internal monitoring of time errors, and internal parameters of the atomic oscillator. The user may set thresholds of any monitored parameter to trigger an alarm.

A precision 1PPS time mark is available for synchronizing or calibrating other equipment and the IRIG B serial time code allows synchronization to be distributed to other computers, displays, and related equipment requiring precise time.

An ASCII serial port outputs any user-selected time of day message at a 1/sec rate for synchronizing other equipment. The same output port may also be configured to output 50 bit/sec BCD time code in accordance with ICD-GPS-060.

A high stability 10MHz sine wave output provides an ultra-stable, low phase noise frequency reference derived from an SC cut crystal that is locked to the rubidium reference.

PTS-SAASM Specifications

1 PPS Output

Connector	SMA
Type	5V _{0-pk} , 10 microseconds wide
On Time	Rising edge

Serial Interface

Port Function	Setup and Control
Connector	DB9
Type	RS232
Baud Rate	300-115,200 (Default 115k N, 8, 1)

Sine Wave Output

Number of outputs	1
Connector	SMA
Frequency	10 MHz
Level	2.5 Vpp into 50 Ohms
Harmonic Distortion	<25 dBc
Phase Noise (SSB)	<-130 dBc/Hz (10Hz) typical <-140 dBc/Hz (100Hz) typical <-150 dBc/Hz (1000 Hz) typical

Time Code Output 1

Number of Outputs	1
Code Format (link sel)	IRIG B 1kHz or DC level
Level	2.2 Vpp 600 Ohms HCMOS
Connector	SMA

Time Code Output 2

Number of outputs	1
Code format	50 bit BCD ICD-GPS-060 or ASCII
Level (link selectable)	RS-232 (4,800, N, 8, 1) or BCD
Connector	DB-9
ASCII format	1/sec user-programmable string

Fault Alarm Status

Output Type	HCMOS level
Output polarity	User programmable
Connector	DB-9

Environmental

Temperature Instrument	0 to + 50°C
Antenna	-40 to +85°C
Humidity	To 95% non-condensing
Power	110/230 Vac
Optional Power	24 Vdc, -48 Vdc, 125 Vdc
Dimensions	3.25" x 7.25" x 15.8"
With rack mount adapter	19 inch Rack Mount, 3.48" (2U) height, 15.80" depth in rack
Weight	5.5 pounds, typical

P(Y) Code GPS Receiver Specification

Receiver Type	GRAM SA-ASM receiver
Satellite Signal	GPS L1, L2 Dual Frequency
Satellite Code	C/A, P(Y)
Receiver Type	Parallel 12 Channel 12 all-in-view receiver
Position Accuracy	16m SEP in SA/AS environment with respect to WGS-84 with CV loaded
Warm start	<120 seconds with Almanac, CV loaded
Anti-spoofing	Accuracy maintained in spoofing environment up to 10db> satellite signals
Jamming	Operates with 34dB J/S at both L1 and L2
Cold Start Requirement	Automatic. No input of time or position required.
CV Fill compatibility	DS102 (KYK-13)
Timing Accuracy	
Tracking satellites	±100 ns. Absolute UTC Std Deviation 20 ns
Holdover Mode	One microsecond/day

Frequency Stability

Tracking satellites	See table below
Holdover Mode	
Aging	<5x10 ⁻¹¹ /month after 30 days aging
Temperature	1x10 ⁻¹⁰ 0 to 50°C

OSCILLATOR STABILITY/ °C	AVERAGING TIME					
	1S	10S	100S	1kS	10kS	1 DAY
2X10 ⁻¹²	2X10 ⁻¹¹	1X10 ⁻¹¹	2X10 ⁻¹²	1X10 ⁻¹²	1X10 ⁻¹²	1X10 ⁻¹²

Ethernet Interface

Type	100BaseT
Connector	RJ45
Protocols Supported	NTP (RFC1305), SNTP, Daytime
Web Browser	5 pages Status, GPS, Configuration, Alarms, Charts
IP selection	Static or Dynamic via DHCP
Protocols	Daytime, Telnet, FTP, DHCP, Time

Other Brandywine Communications Products

FTSU-100 Frequency Synthesizer Distribution Amplifier

Time/message displays

Video Time/message inserters

Timing plug in's for CPCI, PCI, PC104, VME, PMC and ISA platforms

Time and Frequency distribution

Low Cost Network Time Servers

